









OHSAS 18001 NO:K033008

ISO 9001 NO.954596

		140.334330	140.771473	140.R003000
MODEL		PX9020		
Country of origin		South Kor	ea	
ENGINE				
Make		Perkins		
Model		1104C-44TT		
mose.		5/40/40/00/00/00/00/00/00/00/00/00/00/00/		
Туре		4Cyl., In-line Vertical, Water-cooled, Turbo Charge Diesel Engine		
Engine Gross Power	Gross Power HP(kw)		89.2(66.5)	
No. Of Cylinders		4		
Displacement	cc(cu in.)	4399(269	4399(269)	
Rated Revolution	rpm	2200		
PTO	HP(kw)rpm	72.7(54.2) 540/1000 (Independent)		
Fuel tank Capacity	ℓ(us gal)	120(31.7)		
DRIVE TRAIN				
Speeds		16×16		
Differential Lock		Rear Standard		
Shuttle Type		Synchromesh		
Steering		Power Steering		
Main Clutch type		Dry Single Plate - Single Stage Type		
Brake		Wet Disc Type		
Front Wheel Drive System		4WD - Hydraulic		
HYDRAULIC SYSTEM	1.			
3 Point Lift Control Type		Position, Draft, Mix	ed Control	
Pump Capacity Ipm(cc/rev)		48.4(22)		
Power Steering Pump	lpm(cc/rev)	30.8(14)		
otal Hydraulic Flow lpm(cc/rev)		79.2(36)		
3-Point Hitch Type		Category		
Lift Capacity At Lift Point	kg.f(lbs)	2400(529	1)	
Drawbar Type		Drawbar		
No. Of Standard Remote Valves		2		
TIRE SIZE				
AG Tire				
Front		12.4-24, 8	PR	
Rear		18.4-30, 8	PR	
Traveling Speeds				
Forward	km/h(mph)	0.82~38.36(0.51		
Reverse	km/h(mph)	0.67~31.32(0.42	2~19.46)	
OTHERS				
Tilt Steering		Std		
One-Touch Hood Type		Std		
Panel Type		Electric		
DIMENSIONS				
Overall length (w/o front weight and w/o 3pt hitch	n) mm(in)	3935(154.		
Overall length (w/o front weight and w/3pt hitch)	mm(in)	4120(162.		
Overall length (w/front weight and w/3pt hitch) mm(in)		4535(178.5)		
Overall width (minimum tread)	mm(in)	2000(78.7	*	
Tread width - Front	mm(in)	1510(59.5	- 5	
Tread width - Rear	mm(in)	1535(60.4		
Overall height(ROPS) mm(in)		2950(116.0)		
Wheel base mm(in)		2305(90.7)		
Ground Clearance mm(in)		475(18.7)		
Turning Radius(W/O Brake)	mm(in)	4400(173.		
Turning Radius(W/Brake)	mm(in)	3900(153.		
Weight with ROPS	kg.f(lbs)	3500(7716	.2)	

Standard Equipment

- 4WD
- Auto 4WD
- Rear PTO
- · Front weights
- Rear Remote Hydraulic Valve (2pcs)
- Joystic Valve
- AUTO PTO
- · Draft Control
- · Rear View Mirror · Parking Brake
- Battery
- Horn
- 7 Pin Socket
- · Rear Work Light
- Signal Lamp
- · Fuel Tank Cab
- PTO Cover
- · Sun canopy

Optional Equipment

- Rear weights 2pcs × 46kg (92kg)
- · Additional hyd. Lift Cylinder



*NOTE: Specifications and design are subject to change without notice.



PT. AGRITAMA MULTI SARANA

Distributor & Supplier

Equipments & Supplies For Plantations, Agriculture & Forestry

Jl. A. Yani Km. 12,360 No. 168 RT. 002 RW. 001, Gambut Barat – Gambut, Kab. Banjar
Banjarmasin 70652 – Kalimantan Selatan, Indonesia Telp: (0511) 4281876, 4281898,
Fax: (0511) 4283717 E-mail: ams_bim@yahoo.com